

# Lampson Millennium 4600

Crawler Crane



# Lampson

# Millennium 4600

Max. Capacity - Series 5 - 350 US Tons Conventional / 750 US Tons Ringer Attachment  
Max. Line Pull Main Drum - 65,000 lbs  
Max. Line Pull Aux. Drum - 65,000 lbs  
Maximum erected Main Boom Length - 310' Conventional / 400' Ringer  
Maximum erected Main Boom and Jib Length - 260-80 Conv, / 380-120-40 Ringer  
Max. Spooling Capacity Main Drum - Varies by Wire Rope Diameter up to 3,905'  
Max. Spooling Capacity Aux. Drum - Varies by Wire Rope Diameter up to 2,886'  
Max. Line Speed - Varies by Wire Rope Diameter and layer up to 400' per minute  
Ability to accept Manitowoc Ringer® and Tower® attachments with no Modifications  
Tandem Drum Operation for endless reeving  
Meets FedOSHA requirements for Man Basket Suspension - No Freefall Capability



Cummins QSM Tier 3 /4i Engines meet  
Strict Emission Standards



Hydraulic Hoist, Swing and Boom



Newest Generation Comer Industries  
Driven Drums



Computerized Control Systems



Ergonomic Cab with Fingertip Control



Increased Operator Visibility

The Lampson 4600 Millennium Crawler Crane combines the structural integrity and versatility of the Manitowoc 4600 with the safety and ease of operation of the new generation hydraulic operating system cranes. The modernized power train consists of an eco-friendly Tier 3/4i Cummins Engine driving state-of-the-art Comer drum planetaries. Operating controls have been modernized with computer enhanced electronic joysticks controlling all operating functions of the crane. The control system allows tandem drum operating abilities for situations requiring endless reeving. All Millennium series cranes are equipped with LSI load monitoring systems to further enhance safe lift operations.

The Lampson Millennium Crawler Crane meets or exceeds the capabilities of all cranes in the 350 ton capacity class. Offered at a more economical price point, these cranes ensure your projects the utmost in safety, reliability, and cost savings. By utilizing the available Manitowoc Ringer® heavy lift attachment, the capacity can be increased to a maximum of 750 US tons. The Lampson 4600 Millennium also accepts the Manitowoc Tower® attachment to increase available hook height and reach capabilities.

[www.lampsoncrane.com](http://www.lampsoncrane.com)



For Lease or Sales Information Contact any of our Worldwide Locations:

Lampson Corporate Headquarters (Kennewick, WA USA) - (509) 586-0411  
Denver, Colorado Branch Office - (303) 286-1000  
Houston, Texas Branch Office - (713) 674-2531  
Phoenix, Arizona Branch Office - (602) 237-2080  
Lampson Canada Headquarters (Beiseker, AB) - (403) 947-2222  
Lampson Australia Headquarters (Toronto, NSW) - 011 61249 5962222  
or email [info@lampsoncrane.com](mailto:info@lampsoncrane.com)